

<b>UNI-FLEX Model Number</b>	<b>Conveyor Width</b>	<b>Standard Length Compacted - Expanded</b>	<b>Leg Sets per Unit</b>	<b>Skate Wheels per Axle</b>	<b>Load Capacity per linear metre</b>	<b>Approx. Shipping Weight</b>
UFG/SWS/0450/02.50	450 mm	625 mm – 2,500 mm	3	7	300 kg	72 kg
UFG/SWS/0450/03.75	450 mm	940 mm – 3,750 mm	4	7	300 kg	103 kg
UFG/SWS/0450/05.00	450 mm	1,250 mm – 5,000 mm	5	7	300 kg	134 kg
UFG/SWS/0450/06.25	450 mm	1,560 mm – 6,250 mm	6	7	300 kg	165 kg
UFG/SWS/0450/07.50	450 mm	1,880 mm – 7,500 mm	7	7	300 kg	196 kg
UFG/SWS/0450/08.75	450 mm	2,190 mm – 8,750 mm	8	7	300 kg	227 kg
UFG/SWS/0450/10.00	450 mm	2,500 mm – 10,000 mm	9	7	300 kg	258 kg
UFG/SWS/0600/02.50	600 mm	625 mm – 2,500 mm	3	9	300 kg	81 kg
UFG/SWS/0600/03.75	600 mm	940 mm – 3,750 mm	4	9	300 kg	116 kg
UFG/SWS/0600/05.00	600 mm	1,250 mm – 5,000 mm	5	9	300 kg	151 kg
UFG/SWS/0600/06.25	600 mm	1,560 mm – 6,250 mm	6	9	300 kg	186 kg
UFG/SWS/0600/07.50	600 mm	1,880 mm – 7,500 mm	7	9	300 kg	221 kg
UFG/SWS/0600/08.75	600 mm	2,190 mm – 8,750 mm	8	9	300 kg	256 kg
UFG/SWS/0600/10.00	600 mm	2,500 mm – 10,000 mm	9	9	300 kg	291 kg
UFG/SWS/0750/02.50	750 mm	625 mm – 2,500 mm	3	11	300 kg	90 kg
UFG/SWS/0750/03.75	750 mm	940 mm – 3,750 mm	4	11	300 kg	129 kg
UFG/SWS/0750/05.00	750 mm	1,250 mm – 5,000 mm	5	11	300 kg	168 kg
UFG/SWS/0750/06.25	750 mm	1,560 mm – 6,250 mm	6	11	300 kg	207 kg
UFG/SWS/0750/07.50	750 mm	1,880 mm – 7,500 mm	7	11	300 kg	246 kg
UFG/SWS/0750/08.75	750 mm	2,190 mm – 8,750 mm	8	11	300 kg	285 kg
UFG/SWS/0750/10.00	750 mm	2,500 mm – 10,000 mm	9	11	300 kg	324 kg
UFG/SWS/0900/02.50	900 mm	625 mm – 2,500 mm	3	13	300 kg	99 kg
UFG/SWS/0900/03.75	900 mm	940 mm – 3,750 mm	4	13	300 kg	142 kg
UFG/SWS/0900/05.00	900 mm	1,250 mm – 5,000 mm	5	13	300 kg	185 kg
UFG/SWS/0900/06.25	900 mm	1,560 mm – 6,250 mm	6	13	300 kg	228 kg
UFG/SWS/0900/07.50	900 mm	1,880 mm – 7,500 mm	7	13	300 kg	271 kg
UFG/SWS/0900/08.75	900 mm	2,190 mm – 8,750 mm	8	13	300 kg	314 kg
UFG/SWS/0900/10.00	900 mm	2,500 mm – 10,000 mm	9	13	300 kg	357 kg

**Adjustable Height:** The working height of UNI-FLEX Gravity Skate Wheel Conveyors is infinitely adjustable from 740 mm to 1065 mm. If your application requires a specific height, please contact us for further assistance.

**Axle Centre Distances:** When expanded, the distance between axle centres is 125 mm. As an option, 75 mm and 100 mm axle centre distances are available. The optional axle centre distances affect the compacted conveyor length. Please contact us for further assistance.

**Extended Lengths:** UNI-FLEX Gravity Skate Wheel Conveyors are available in any length. If your application requires a length that is not listed in the above chart, please contact us for further assistance.