

UNI-FLEX Model Number	Conveyor Width	Standard Length Compacted - Expanded	Leg Sets per Unit	Rollers per Axle	Load Capacity per linear metre	Approx. Shipping Weight
UFG/ROS/0450/02.50	450 mm	835 mm – 2,500 mm	3	2	250 kg	78 kg
UFG/ROS/0450/03.75	450 mm	1,250 mm – 3,750 mm	4	2	250 kg	112 kg
UFG/ROS/0450/05.00	450 mm	1,670 mm – 5,000 mm	5	2	250 kg	146 kg
UFG/ROS/0450/06.25	450 mm	2,080 mm – 6,250 mm	6	2	250 kg	180 kg
UFG/ROS/0450/07.50	450 mm	2,500 mm – 7,500 mm	7	2	250 kg	214 kg
UFG/ROS/0450/08.75	450 mm	2,920 mm – 8,750 mm	8	2	250 kg	248 kg
UFG/ROS/0450/10.00	450 mm	3,330 mm – 10,000 mm	9	2	250 kg	282 kg
UFG/ROS/0600/02.50	600 mm	835 mm – 2,500 mm	3	2	250 kg	89 kg
UFG/ROS/0600/03.75	600 mm	1,250 mm – 3,750 mm	4	2	250 kg	128 kg
UFG/ROS/0600/05.00	600 mm	1,670 mm – 5,000 mm	5	2	250 kg	167 kg
UFG/ROS/0600/06.25	600 mm	2,080 mm – 6,250 mm	6	2	250 kg	206 kg
UFG/ROS/0600/07.50	600 mm	2,500 mm – 7,500 mm	7	2	250 kg	245 kg
UFG/ROS/0600/08.75	600 mm	2,920 mm – 8,750 mm	8	2	250 kg	284 kg
UFG/ROS/0600/10.00	600 mm	3,330 mm – 10,000 mm	9	2	250 kg	323 kg
UFG/ROS/0750/02.50	750 mm	835 mm – 2,500 mm	3	2	250 kg	100 kg
UFG/ROS/0750/03.75	750 mm	1,250 mm – 3,750 mm	4	2	250 kg	144 kg
UFG/ROS/0750/05.00	750 mm	1,670 mm – 5,000 mm	5	2	250 kg	188 kg
UFG/ROS/0750/06.25	750 mm	2,080 mm – 6,250 mm	6	2	250 kg	232 kg
UFG/ROS/0750/07.50	750 mm	2,500 mm – 7,500 mm	7	2	250 kg	276 kg
UFG/ROS/0750/08.75	750 mm	2,920 mm – 8,750 mm	8	2	250 kg	320 kg
UFG/ROS/0750/10.00	750 mm	3,330 mm – 10,000 mm	9	2	250 kg	364 kg
UFG/ROS/0900/02.50	900 mm	835 mm – 2,500 mm	3	2	250 kg	111 kg
UFG/ROS/0900/03.75	900 mm	1,250 mm – 3,750 mm	4	2	250 kg	160 kg
UFG/ROS/0900/05.00	900 mm	1,670 mm – 5,000 mm	5	2	250 kg	209 kg
UFG/ROS/0900/06.25	900 mm	2,080 mm – 6,250 mm	6	2	250 kg	258 kg
UFG/ROS/0900/07.50	900 mm	2,500 mm – 7,500 mm	7	2	250 kg	307 kg
UFG/ROS/0900/08.75	900 mm	2,920 mm – 8,750 mm	8	2	250 kg	356 kg
UFG/ROS/0900/10.00	900 mm	3,330 mm – 10,000 mm	9	2	250 kg	405 kg

Adjustable Height: The working height of UNI-FLEX Gravity Roller Conveyors is infinitely adjustable from 730 mm to 1055 mm. If your application requires a specific height, please contact us for further assistance.

Axle Centre Distances: When expanded, the distance between axle centres is 125 mm. As an option, 75 mm and 100 mm axle centre distances are available. The optional axle centre distances affect the compacted conveyor length. Please contact us for further assistance.

Extended Lengths: UNI-FLEX Gravity Roller Conveyors are available in any length. If your application requires a length that is not listed in the above chart, please contact us for further assistance.